


Accessories—One-Touch Fittings

One-touch fittings—threaded type

Ordering code

BB 01 01 □

① ② ③ ④

① Model	② Thread connection I	③ Thread connection II	④ Thread type
BB: Male connector 	BD: Male & female connector[Note1] 	BU: Double female connector 	BZ: Hexagon head cap plug[Note2] 
	01 : 1/8" 02 : 1/4" 03 : 3/8" 04 : 1/2"	01 : 1/8" 02 : 1/4" 03 : 3/8" 04 : 1/2"	Blank: PT

[Note1] For BD series, Thread I is Female thread, Thread II is male thread; [Note2] For BZ series, no thread II and thread I is male thread.

Specification

Operating pressure range	0~10kgf/cm ² (0~1.0MPa)
Negative pressure	-750mmHg(10Torr)
Proof pressure	3.0MPa
Ambient and fluid temperature (°C)	0~150

Product feature


1. Variable models can be widely used in every kind of pneumatic systems.
2. High circulation performance bear the same flow with the volume of the tube innerdiameter.
3. The nickel plated body is anti-corrosion and anti-pollution, which allows a broader application.
4. Nickle plated mental body is resistant to corrosion and pollution, which has wider range of application.

Dimensions

Configuration table of tubing thread


Product series	Thread connection I	Thread connection II			
		01	02	03	04
BB	01	●	●	●	
	02		●	●	●
	03			●	●
	04				●
BD	01		●	●	●
	02			●	●
	03				●
	04				
BU	01	●			
	02		●		
	03			●	
	04				●
Product series	Thread connection				
	01	02	03	04	
BZ	●	●	●	●	

BB Series




Model\Item	RA	RB	LA	LB	C	H	Weight(g)
BB0101	1/8"	1/8"	7.5	7.5	19.5	10	6.6
BB0102	1/4"	1/8"	10	7.5	22.5	14	12.1
BB0103	3/8"	1/8"	11	7.5	24	17	18.3
BB0202	1/4"	1/4"	10	10	25	14	14.6
BB0203	3/8"	1/4"	11	10	26.5	17	20.3
BB0204	1/2"	1/4"	14	10	30	21	34.3
BB0303	3/8"	3/8"	11	11	27.5	17	23.2
BB0304	1/2"	3/8"	14	11	31	21	36.2
BB0404	1/2"	1/2"	14	14	34	21	42.8

BD Series




Model\Item	RA	RB	LA	LB	C	H	Weight(g)
BD0102	1/4"	1/8"	10	8	14.5	14	8.8
BD0103	3/8"	1/8"	11	8	16	17	17.1
BD0104	1/2"	1/8"	14	8	19.5	21	33.1
BD0203	3/8"	1/4"	11	11	16	17	12.7
BD0204	1/2"	1/4"	14	11	19.5	21	29.9
BD0304	1/2"	3/8"	14	12	19.5	21	22.5

BU Series



Model\Item	R	L	C	H	Weight(g)
BU0101	1/8"	8	17	14	4.7
BU0202	1/4"	11	23	17	8.1
BU0303	3/8"	12	25	21	12.7
BU0404	1/2"	13.5	28	25	18.0

BZ Series



Model\Item	R	L	C	H	Weight(g)
BZ01	1/8"	7.5	11	10	4.6
BZ02	1/4"	10	14.5	14	10.8
BZ03	3/8"	11	16	17	17.4
BZ04	1/2"	14	19.5	21	33

One-touch fittings—threaded type

Ordering code

BKC 06 04 - 01 □

① ② ③ ④ ⑤

① Model	② Tubing outer diameter	③ Tubing inner diameter	④ Thread connection	⑤ Thread type
BKC: Straight locknut connector 	04 : Φ4mm 06 : Φ6mm 08 : Φ8mm 10 : Φ10mm 12 : Φ12mm	25 : Φ2.5mm 04 : Φ4mm 05 : Φ5mm 06 : Φ6mm 65 : Φ6.5mm 75 : Φ7.5mm 08 : Φ8mm 09 : Φ9mm	M3 : M3X0.5 M5 : M5X0.8 01 : 1/8" 02 : 1/4" 03 : 3/8" 04 : 1/2"	Blank: PT

Note: When using the tubing Φ8×Φ5.5, the straight lock nut connector of BKC0806 can be used.

Specification

Operating pressure range	0~10kgf/cm ² (0~1.0MPa)
Negative pressure	-750mmHg(10Torr)
Proof pressure	3.0MPa
Ambient and fluid temperature (°C)	0~150


Note: The temperature resistance level of the tubing should be confirmed first when used in high temperature environments.

Product feature

1. Variable models can be widely used in every kind of pneumatic systems.
2. High circulation performance bear the same flow with the volume of the tube inner diameter.
3. The nickel plated body is anti-corrosion and anti-pollution, which allows a broader application.
4. Metal fittings can be used in high temperature environments.

Dimensions

BKC Series



Model\Item	Tubing diameterΦD		R	L	C	K	G	H	Weight(g)
	O.D	I.D							
BKC0425-M3	4	2.5	M3×0.5	3	17	5	8	8	4.4
BKC0425-M5			M5×0.8	3.5	17.5			8	4.8
BKC0425-01	6	4	1/8"	7.5	20.5	5.5	10	10	7.1
BKC0604-01			1/8"	7.5	22			10	9.9
BKC0604-02			1/4"	10	25.5			14	15.8
BKC0604-03	8	5	3/8"	11	27	6.5	12	17	22.5
BKC0805-01			1/8"	7.5	24			12	12.8
BKC0805-02			1/4"	10	27.5			14	17.2
BKC0805-03		5.5 or 6	3/8"	11	29			17	23.7
BKC0806-01			1/8"	7.5	24			12	13.1
BKC0806-02			1/4"	10	27.5			14	17.2
BKC0806-03			3/8"	11	29			17	23.6

Model\Item	Tubing diameterΦD		R	L	C	K	G	H	Weight(g)
	O.D	I.D							
BKC1065-02	10	6.5	1/4"	10	30	7.5	15	15	25.3
BKC1065-03			3/8"	11	31.5			17	29.1
BKC1065-04		7.5 or 8	1/2"	14	35.5			21	44
BKC1075-02			1/4"	10	30			15	24.1
BKC1075-03	12	8	3/8"	11	31.5	7.5	17	17	28.9
BKC1075-04			1/2"	14	35.5			21	43.6
BKC1208-02		9 or 10	1/4"	10	30			17	30.5
BKC1208-03			3/8"	11	31.5			17	32.1
BKC1208-04			1/2"	14	35.5			21	46.7
BKC1209-02		10	1/4"	10	30			17	30.6
BKC1209-03			3/8"	11	31.5			17	31.9
BKC1209-04			1/2"	14	35.5			21	46.4

Installation and application

1. Method of inserting or removal a tubing

1.1 Inserting a tubing

Place the locking cap over the tubing, and insert the tubing into the body, then tighten the locking cap. (As figure 1)

1.2 Removing a tubing

Loosen the locking cap first, then remove the tubing. (As figure 2)

2. Method of tightening the connector thread

Tighten the connector with a hex wrench, as shown right.




Figure 1




Figure 2




Figure 3